

Product Specification Sheet



600kW Boiler

High Efficiency oil fired LTHW boiler.

Product Benefits

- Fully packaged, Containerised unit
- Easy to use controls
- Secondary circuit with large expansion tank built in
- Easily manoeuvrable

Technical Data

15-05-2025 | 07:05:17

EL-BJORN UK LTD

Unit 2 Oyster Park, 109 Chertsey Road,
West Byfleet, GB-Surrey, KT14 7AX
Phone: (+44) 01483 729 348
E-mail: info@elbjorn.com



Product name	600kW Boiler
Product Number	GB80057H
Heating Output	600 kW
Temperature Range	20-82 °C
Primary Expansion Tank	80 L
Secondary Expansion Tank	500 L
Total System Volume	820 L
Minimum Working Pressure	1 Bar
Maximum Working Pressure	9 Bar
Flow Rate	32 m³/hr
Max Fuel Consumption	61.7 LPH
Fuel Efficiency	94 %
DHW Circuit Module	Optional
Fuel Type	Oil
Electrical Feed	400/3/50 + N + E v/ph
Maximum Absorbed Current (FLA)	9.8 A
Dimensions H x W x D (mm)	3700 x 2000 x 2332
Weight (Empty)	3700 Kg
Fluid Connections	Flange (4" Camlock Option) Inch

15-05-2025 | 07:05:17