Product Specification Sheet





16A – 63A Harsh Environment Socket Assembly

16A - 63A Harsh Environment Socket Assembly

El-Bjorn UK designs and manufacturers Multi-Voltage Industrial Socket Outlet Assemblies (MVSA) to BS EN 60309-2, rated from 16A to 125A, in single or three-phase varieties.

The outlet assembly range are a custom designed product series, built to the customer's exact specification and can incorporate isolator, RCD, kWHr meters with or without MCB overcurrent protection. Hardwired outlets and non-standard outlets are also available. This enclosure benefits from two rows available for protective devices.

Switched interlocking is possible for areas where uninstructed persons may be operating the equipment and to prevent the insertion or withdrawal of plugs on load, and for applications where switched interlocking is required by BS7375 for construction site applications.

This particular product is designed for harsh construction or industrial environments. All El-Bjorn MVSA products come with a 5 year warranty.



17-11-2025 | 20:02:08



E-mail: info@elbjorn.com

Unit 5 Beacon Hill Logistics Park, Beacon Hill Road, Church Crookham, Fleet, Hampshire, GU52 8DY Phone: (+44) 01483 729 348



Product Benefits

- Custom configured Multi Voltage Socket Assembly (MVSA)
- Socket outlets to BS EN 60309-2
- Powder coated finish in Blue (insulated and stainless steel versions available)
- IP44 and IP67 versions available
- Available for purchase POA

Technical Data

Product name	16A – 63A Harsh Environment Socket Assembly
Product Number	EB2467426
Rated current	16A - 63A
Voltage	400V
Incoming Connectable area Al/Cu	4 mm² - 35 mm²
RCD	30mA - 500mA (instantaneous or time delayed
Dimensions (H x W x L) mm	530 x 290 x 258
Short-circuit strength Icc	6kA
Weight (kg)	Enclosure weight based on configuration
IP rating	IP44 and IP67 versions available

17-11-2025 | 20:02:08

