

Product Specification Sheet



HRFW-60 Stage 5 Generator

The HRFW-60 is one of our medium sized Stage V(5) Diesel Generator, producing a total power output of 59kVA, fitted with 1 x 16A 230V 2P+E, 3 x 32A 400V 3P+N+E, 1 x 63a 400V 3P+N+E sockets and a 216ltr internal bunded fuel tank for short term power generation (recommended to be used with additional bunded fuel tank for continuous use). Our Stage V(5) Diesel Generators have been specifically designed to be compliant with EU Regulation 2016/1628/CE. Using a sophisticated built in exhaust treatment system, these generators clean the fumes expelled by the engine before they are released into the atmosphere. This process provides a reduction of up to 90% of environmentally hazardous gases and particles compared to previous technology. This generator is perfectly suited as a temporary power source for medium sized projects on construction sites, temporary work spaces, industrial areas and events venues with access to outside space.

20-05-2024 | 03:29:08

EL-BJÖRN UK LTD

Unit 2 Oyster Park, 109 Chertsey Road,
West Byfleet, GB-Surrey, KT14 7AX
Phone: (+44) 01483 729 348
E-mail: info@elbjorn.com



Product Benefits

- 59kVA Stage V Diesel Generator
- 216ltr Metal Bunded Fuel Tank
- Socket Pack - 1 x 16A 230V 2P+E, 3 x 32A 400V 3P+N+E, 1 x 63a 400V 3P+N+E

Technical Data

Product name	HRFW-60 Stage 5 Generator
Product Number	GEN60S5
Power Output	59kVA
Internal Metal Bunded Fuel Tank	216ltr
Engine	Iveco - Stage V Diesel Engine
Filter	Racor filter with alarm
Alternator	Stamford Alternator - UCI224E
Breaker	Schneider 4P 80AMP Type 'D' Manual Breaker
Fuel Valve	3 Way
Socket Pack	1 x 16A 230V 2P+E, 3 x 32A 400V 3P+N+E, 1 x 63a 400V 3P+N+E
Additional	DSE890 Gateway & Antenna

20-05-2024 | 03:29:08