

Product Specification Sheet



SMDU-125A-4W

Socket Mains Distribution Unit (SMDU) made from powder coated aluminium. The unit is freestanding on a tubular aluminium folding stand and has fixing points for wall mounting, the unit also has top mounted carry handles for ease of handling and transportation. All components are accessible from behind the front padlockable door, this unit can form part of a robust and secure plug and play system suitable for a range of applications, including construction sites, industrial areas, events spaces and exhibitions.

Input: 1mtr H07RN-F cable with a 125A 5P 400V IP44 commando inlet to BS EN 60309-2 with MCB for overcurrent and isolation purposes.

Output: 4no 32A 5P 400V IP44 commando socket outlets to BS EN 60309-2, each supplied by a C32A 30mA 6kA 4P 30 mA RCBO.



31-08-2025 | 17:45:08

EL-BJORN UK LTD

Unit 2 Oyster Park, 109 Chertsey Road,
West Byfleet, GB-Surrey, KT14 7AX
Phone: (+44) 01483 729 348
E-mail: info@elbjorn.com



Product Benefits

- Built using durable and lightweight powder coated aluminium
- Comes complete with fitted tubular stand
- Corrosion resistant side hinged padlockable door
- High quality Schneider switchgear
- High quality ABB branded socket outlets and input plug
- Patent protected withdrawable main body for ease of servicing/maintenance

Technical Data

Product name	SMDU-125A-4W
Product Number	EB16697
Construction	Aluminium-Powder Coating
Colour	El-Björn Blue
Dimensions (mm)	910 x 570 x 310
IP Rating	IP44
Short Circuit Rating kA	6kA

31-08-2025 | 17:45:08