Product Specification Sheet





KH2.5 110V

The KH2.5 110V portable heater is our smallest and most versatile Cube Heater. Designed for temporary or permanent heating, the KH2.5 110V is fitted with a 110V, 3 pin, 32 Amp plug, ideal for use in; warehouses, workshops, constructions sites, industrial areas, event spaces and similar areas.

Equipped with a large connection collar that allows for the connection of additional ductwork to help better direct the flow of warm air to specific areas. The KH2.5 portable heater produces a high airflow with minimal noise and is equipped with a mechanical thermostat allowing you to control the room temperature. The overheating protection technology allows the heater to safely run unattended without overheating within a dry work environment.



11-08-2025 | 06:24:40



E-mail: info@elbjorn.com



Product Benefits

- Mechanical thermostat for room temperature control
- Overheating protection
- High air flow with low noise

Technical Data

Product name	KH2.5 110V
Product Number	EB16583
Rated current	18A
Voltage	1N-110V
Plug type	110V, 3 pin, 32 Amp plug
Total heat output (kW)	2
Power setting (kW)	2
Airflow (m³/h)	375
Temperature increase	45°C
Noise level (dB(A))	52.8
Weight (kg)	11
Dimensions HxWxL (mm)	333x299x274
Protection rating	IP44
Average seasonal efficiency	36%

11-08-2025 | 06:24:40

