# Product Specification Sheet




## P1-125A MRCD-8W

**Premium Enclosure: 125A 4P MCB+VARI RCD feeding 8W Pan.**
This Premium Pan-Assembly Distribution Panels are engineered for robust temporary power distribution on construction sites, industrial projects, and commercial buildings. This 125A configuration offers a 4P MCB+VARI RCD incoming device feeding an 8W Three Phase MCB Pan-Assembly. The pan assembly will accommodate 8 no. TP MCBs, 24 no. SP MCBs or 24 no. RCBOs, or combination of the three. The pan accepts Schneider Acti9 iC60 series devices. All ways are supplied blanked-off.
Designed with flexibility in mind, the panels are manufactured with an internal DIN rail allow for the mounting of additional devices such as RCDs, time clocks, and contactors, ensuring adaptability on-site.
Manufactured in our UK assembly facility, this Premium Enclosure is constructed from durable, corrosion-resistant galvanised steel, Built to BS EN (IEC) 60439-4 standards, offer reliable performance in tough, high-demand environments like construction zones. Features also include heavy-duty stainless steel hinges and a secure padlock latch to prevent unauthorised access and unwanted unit downtime.

22-11-2026 | 12:56:30

**EL-BJÖRN UK Ltd**
Unit 5 Beacon Hill Logistics Park, Beacon Hill Road, Church Crookham,
Fleet, Hampshire, GU52 8DY
Phone: (+44) 01483 729 348
E-mail: info@elbjorn.com

## Product Benefits

- 125A 4P MCB+VARI RCD feeding 8W Pan
- 8 Ways
- Galvanised sheet steel with powder coating finish
- Stainless steel hinges and heavy-duty padlock latch
- Schneider branded Pan-Assembly
- Supply of spare parts supported
- Customised versions available at additional cost
- Customised versions available at additional cost
- Contact us directly for purchases

## Technical Data

| | |
|---|---|
| **Product name** | P1-125A MRCD-8W |
| **Product Number** | EB12791E |
| P1 Enclosure Specification | 125A 4P MCB+VARI RCD feeding 8W Pan |
| Dimensions with stand H x W x D (mm) | 1380 x 705 x 600 |
| Dimensions without stand H x W x D (mm) | 785 x 705 x 180 |
| Number of Module Ways | 8 |
| Incomer Rating | 125A |
| Maximum Current Rating | 125A |



**EL-BJÖRN UK Ltd**
Unit 5 Beacon Hill Logistics Park, Beacon Hill Road, Church Crookham,
Fleet, Hampshire, GU52 8DY
Phone: (+44) 01483 729 348
E-mail: info@elbjorn.com