Product Specification Sheet





TF3 110V

During development of TF3 we have created the most convenient machine on the market in terms of dimensions, weight and performance. Fitted with a 110V, 3 pin, 32 Amp plug, the TF3 delivers a full 2.8 kW of heating from an power overall consumption of just 3 kW. With the ability to be used both indoors or outdoors, the TF3 is adaptable for a multitude of applications from industrial and construction sites to warehouses and event spaces.

This heating and drying fan includes a continuous thermostat, variable between 5–45 degrees C, with automatic overheating protection. The TF3 is able to spread heated air over 360 degrees of direction, thanks to the integrated air distributor, making it a powerful drying fan for floor area of 50–60 square metres.



02-08-2025 | 13:46:47



Unit 2 Oyster Park, 109 Chertsey Road, West Byfleet, GB-Surrey, KT14 7AX Phone: (+44) 01483 729 348 E-mail: info@elbjorn.com



Product Benefits

- Continuously variable thermostat for temperature control in the range 5-45 °C
- Ruggedly constructed from corrosion-resistant galvanised and powder-coated sheet metal
- Stackable design takes up very little space during transport and storage. Designed for pallet delivery
- IP44 protection rating

Technical Data

Product name	TF3 110V
Product Number	EB11773
Plug Type	3-pol/110V 32 A CEE 232-4
Incoming Cable Length / Area Cable / Connector	2m / H07RN-F 3x6 / CEE 232-4
Rated current	27 A
Output modes	3,0 kW
Total thermal power	3,0 kW
Temperature increase	35 °C
Air flow	450 m³/h
Noise level	61 dB(A)
Weight tot	13,2 kg
Dimensions H x W x D (mm)	500 x 295 x 300
Protection class	IP44

02-08-2025 | 13:46:47

